

## Features:

- No grills for a traditional masonry fireplace look.
- Durable, high temperature, 5mm silica coated ceramic glass. Fire viewing area 1050 sq. in. rectangular model. Fire viewing area 998 sq. in. arched model.
- Realistic, five-piece detailed log set cast from real firewood.
- Engage the Manual Heat Damper to release 30% of the heat. This allows for less heat into the room and year-round enjoyment of the fire.
- Digital Home Comfort Control System can be operated by the hand-held remote control and the wireless wall control.
- The Electronic Gas Valve can be run for greater efficiency in the "Intermittent Pilot Mode" with the gas pilot turned off until you need it or "Standing Pilot Mode", with the gas pilot always on, for reliable cold weather operation.
- Natural (NG) or Propane (LP) operation.
- Uses ONLY Simpson Duravent 8 5/8" x 6" chimney.
- Seven Year "Real World" Warranty.

## Framing Dimensions:

 See Installation Manual

- 1.** Hearth Requirements: Extends 10" from face and 49 1/2" wide when installed flush. Not required when raised 6" (See Installation Manual for details)
- 2.** Non-combustible facing.
- 3.** Side Wall Clearance: 10 1/2".
- 4.** Mantle Clearances: 48 1/2" from base of fireplace. Maximum allowed mantle depth: 12"
- 5.** Minimum fireplace enclosure height 82". Measured from base of fireplace. 96" minimum ceiling height in room.
- 6.** Minimum framing: 49 3/4" wide x 56 3/4" tall x 25" deep.
- 7.** The fireplace must be placed on cement board.

Tested and Certified by OMNI-Test Laboratories Inc. to ANSI Z21.88b "Vented Gas-Fired Direct Fireplace Heater".

Must be installed in accordance with all local codes, if any; if not, follow ANSI Z223.1 and the requirements listed in the Owner's Manual.

Note: Improper installation of your gas appliance or failure to operate it in accordance to the guidelines detailed in the Owner's Manual may negate your warranty. We recommend all Fireplace Xtrordinair appliances be installed and maintained on an annual basis by your specialty hearth retailer.

## Natural Gas Input Rating & Performance:

- Adjustable High Heat System:  
28,500 – 50,000 Btu's (NG)  
26,900 – 49,000 Btu's (LP)
- Steady State Efficiency: 74%
- Heater Rated Fireplace: Heats up to 1,200 to 2,000 sq. ft.\*  
\*Heating capacity will vary depending on the temperature zone you live in.

